

NEW!

BECK
Kanal- und Schachtgeräte

Anti clatter insert

(Industrial property rights applied for)

- ▶ The self-hardening damping paste in a bag
- ▶ For all shapes and sizes of clattering covers in all traffic areas
- ▶ Safe and successful noise abatement
- ▶ The high-quality and versatile alternative to the spacer ring



durable, heavy-duty, frost and de-icing salt resistant

- ☒ The safe cover spacer with the particular fit.
- ☒ Prevents clatter noise and is also ideally suited as a seal.
- ☒ Does not inhibit removal of the protective screen during cleaning or when entering the shaft.
- ☒ The damping insert is made from environmentally friendly and cold-setting bicomponent liquid plastic.
- ☒ The paste is injected on the spot directly from the bag into the shaft frame.
- ☒ In fitting the cover the exact and optimal shape is formed.
- ☒ An all-over damping insert is created within minutes.
- ☒ For all shapes and sizes of covers.

über
20
Jahre



NEW!

BECK

Kanal- und Schachtgeräte

Packing unit

Anti clatter insert

Contents of bag: approx. 440 g
enough for: e.g. 1 manhole cover up to
Ø approx. 700 mm or
rectangular covers up to
approx. 200 cm support
length

Article no.: **UR-AK**

Anti clatter insert Mini-pack

Contents of bag: approx.. 220 g
enough for: e.g. 1 Hydrant cover or
1 rain water drain or
1 slide cap or
rectangular covers up to
approx. 100 cm support
length

Article no.: **UR-AK-Mini**

Here's how to be done!

1. Remove the clattering cover from the frame.
2. Clean the surface and cover of coarse dirt.
3. Using a cloth saturated with the stripping agent from the compartment **1**, rub the bottom and sides of the cover lightly and allow stripping agent to act.
4. Release the **bag clamp** between compartments **2** and **3** and remove.
5. Thoroughly mix the two components in the bag by kneading.
6. Cut off a corner of the bag with scissors (approx. 1 cm). Inject the paste from the bag into the shaft frame or support surface by creating a bead approx. 7 mm thick.
7. Place the cover in the frame immediately before the paste hardens. 🖱️ **Ready !**

You can drive over the cover after only a few minutes!



Environmental protection through noise abatement 🖱️ **The optimal solution!**

Beck GmbH

Kanal- und Schachtgeräte

Obere Mühle 11 ▪ 74906 Bad Rappenau ▪ Germany
Tel.: +49 (0) 70 66 / 99 20-0 ▪ Fax: +49 (0) 70 66 / 99 20-20
E-Mail: info@beck-kanal.de
Internet: www.beck-kanal.de

